



# NEROLAC

## BEAUTY PREMIUM ACRYLIC DISTEMPER

### PRODUCT DESCRIPTION

**Nerolac Beauty Premium Acrylic Distemper (NBPAD) is a premium quality, durable, water based interior wall finish. It can be applied on ceilings and walls where a beautifying matt finish, free from irritating glares due to light reflection is desired.**

### PERFORMANCE FEATURES & BENEFITS



### SURFACE PREPARATION

- 1** Ensure the surface is clean, dry and free from all defective or poorly adhering material, dirt, grease, wax, etc.
- 2** Remove all loose or poorly adhering material by rubbing down using suitable abrasive paper and there after wipe off.
- 3** Treat fungus affected area using Nerolac Fungicidal Solution. Allow to react for 6-8 hrs.
- 4** Apply a coat of suitable Primer\* followed by Nerolac wall putty to level the dents and make surface uniform. Apply again a coat of suitable Primer\*.
- 5** Then apply two coats of Nerolac Beauty Acrylic Distemper.

### RECOMMENDED USAGE

Nerolac Beauty Premium Acrylic Distemper is recommended for interior use only. It can be applied on fully matured plaster work, concrete, brickwork and asbestos surfaces where a matt finish, free from irritating glares due to light reflection is desired.

### RECOMMENDED SYSTEM FOR APPLICATION

#### For New Masonry Surfaces

- 1** Primer\* (1 coat) Dry 4
- 2** Putty Nerolac Wall Putty Dry 6-8 hrs.
- 3** Primer\* (1 coat) Dry #
- 4** Finish Nerolac Beauty Premium Acrylic Distemper (2-3 coats)

**Sand the surface with Emery Paper and wipe clean before application on subsequent coats.**

\*Nerolac Cement Primer ( Water Thinnable / Solvent Thinnable) or Goody Universal Primer (Solvent Thinnable) or Goody Water Thinnable Cement Primer.

# Minimum 8 Hrs for Solvent Thinnable Primer & Minimum 4-6 Hrs for Water Thinnable Primer.

**FOR REPAINTING ON SMOOTH LIME/DISTEMPER/ EMULSION / ENAMEL MASONRY SURFACES SKIP STEPS 2 AND 3.**

## TECHNICAL DATA



### COVERAGE \*\*\*

17.66 - 20.45 sq.m./ltr/coat., when applied on smooth and non-absorbent surface.

### GLOSS LEVELS/ SHEEN LEVELS

Matt



### DRYING TIME

Surface Dry: 30 minutes.

### THINNING

Upto 1 ltr of water to 1.5 kg of Distemper.



### RECOATING

Min 4-6 Hrs. @27° ± 2°C & RH 60 ± 5%

### FLASH POINT

NA



### STABILITY OF THINNED PAINT

Use within 24 Hrs.

\*\*Actual coverage may vary depending on method, condition of application, surface roughness & shade.

## PRECAUTIONS



- Refer PDS for 'Nerolac Beauty Premium Acrylic Distemper' for safety measures and precautions.
- Store in well ambient conditions, ventilated locations and away from sources of ignition and fire.
- Keep away from children.
- In case of eye/ skin contact, wash with plenty of water.
- Inhalation / Injection will cause danger. In case move to fresh air & consult medical practitioners in both the cases.
- Do not apply when ambient temperature might drop to level below 10°C within 4 Hrs. of application.
- New plaster should be allowed to cure for minimum 12 weeks.
- Avoid extra thinning for better results.
- Can be tinted with 'Nerolac Hi-Power Universal Stainer' before thinning. Do not add more than 5% of 'Nerolac Hi-Power Universal Stainer'. Stir the tinted paint well, after tinting & before application.
- The container must be tightly closed when not in use. Stir well and strain before use.
- Use safety equipment's like rubber or polythene gloves, safety goggles / glasses and face mask.

## POST APPLICATION INSTRUCTIONS

Surfaces painted with NBPAD are washable by sponging with mild soap and water after a min. of 2 weeks drying to remove ordinary stains and everyday dirt.

## PACK SIZES



1 kg, 2 kgs, 5 kgs, 10 kgs and 20 kgs.

## SAFETY FEATURES



Non- Flammable.

## SHADE RANGE



As per Beauty Range Shade Cards and Colour Scapes Fandek.